

# Product Definition

Refractory Mortars

Product : **TH 1500 H**

Other names : RL26H, RL45H

Maximum classified temperature : **1 500 °C**

Ref-date : 2012-B

Brand Code : H155

Mark on the Buckets : According Name

Properties :	Standards	Units	Average $\mu$	Std. Dev. $\sigma$	Limits	
					Ti (lower)	Ts (upper)
Bulk Density :		T/m <sup>3</sup>				
Maximum grain size :		mm	0.6			
Water		%				
Chemical Analysis :	XRF	%				
Al <sub>2</sub> O <sub>3</sub>			47		45	
SiO <sub>2</sub>			47.5			
Fe <sub>2</sub> O <sub>3</sub>			0.9			1.8
TiO <sub>2</sub>			1.2			
CaO + MgO			0.8			
Na <sub>2</sub> O+K <sub>2</sub> O			2.6			
Cold Modulus Of Rupture :	ISO 5014	MPa				
- After drying			6			
- After firing						
<b>Other Informations :</b>						
Mean quantity useful for 1 m <sup>3</sup> of bricks :		Kg	150			
Description :	Air set mortar Recommended for bricks classes 26 BEWARE : DO NOT FREEZE					
Manufacturing Plant :	LIBOS (F47500)					

Physical properties are based on averages of routine quality control tests carried out through manufacturing. Averages and standard deviations are indicative values, limits (Ti et Ts) are guaranteed values.